

Norfloat International's channel marker buoy is an affordable low-maintenance, high visibility buoy.

Its torispherical bottom design significantly increases its stability in deep, shallow, tidal and drying out conditions. The channel marker buoy is ideal for harbours, in-shore waters, estuaries, rivers, lakes and fjords. Available in port, starboard, special marks and race marks, the channel marker buoy can be fitted with most makes of 1-2nm self-contained lighting units.

Features

UV stabilised polyethylene

Polyethylene offers excellent impact resistance. Its low energy surface reduces marine growth significantly which helps keep maintenance costs to a minimum.

Foam filled

The channel marker buoy has increased wall thickness allowing it to be used with or without foam fill, depending on its application.

Lighting

Optional 1-2nm self-contained lighting can be fitted using a light fitting kit which has been specially designed, making it difficult for it to be stolen.

Mooring connection

The single point mooring eye incorporates a 316 stainless steel wear bush and has been designed to use a 32mm "D" shackle.

Specifications

Product code	CM1100
Diameter	1100mm
Focal height	1000mm
Air weight	without foam 30kg/with foam 50kg
Wall thickness	9 - 15mm

Although every effort is made to provide accurate information, dimensions and weights may vary slightly. Norfloat International reserves the right to change specifications without notice.

