

Polyester

Polyester ropes remain durable and easy to handle even when wet. The ropes are spliced easily into soft eyes for use in mooring lines or lanyards. Polyester doesn't lose strength when wet, it has excellent UV resistance, very good abrasion resistance and will not shrink under normal conditions.

Polyester has a higher specific gravity than Nylon or Polyurethane and it therefore similarly, a shrinking rope.

Polyester ropes manufactured to exceed both British and European Standard published by the European Committee for Standardization, or CEN (BS EN 697: 1995).

Three/ Four Strand Hawser Lay Polyester

Part No	Line Diameter	Reel Size	Break Load (kgs)
NMR000103P	10	220	2290
NMR000123P	12	220	3450
NMR000143P	14	220	4400
NMR000163P	16	220	6000
NMR000183P	18	220	7000
NMR000203P	20	220	8400
NMR000223P	22	220	10800
NMR000243P	24	220	12500



Twelve Strand Plaited Polyester

Part No	Line Diameter	Reel Size	Break Load (kgs)
NMR001012P	10	220	2519
NMR001212P	12	220	3795
NMR001412P	14	220	4840
NMR001612P	16	220	6600
NMR001812P	18	220	7700
NMR002012P	20	220	8140
NMR002212P	22	220	11880
NMR002412P	24	220	13750

